SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Gold Bond® eXP® Sheathing

IDENTIFIERS

Gold Bond® eXP® Sheathing

OTHER MEANS OF IDENTIFICATION

Wallboard, Gypsum Board, Plasterboard, Drywall, Exterior Sheathing, Mold and Moisture Resistant

RECOMMENDED USE

Exterior building walls where moisture is a concern. Use per manufacturer's recommendations.

RESTRICTIONS ON USE

Use in well-ventilated area and avoid breathing dust. Avoid skin contact.

MANUFACTURER/SUPPLIER DETAILS

Gold Bond Building Products, LLC 2001 Rexford Road Charlotte, NC 28211

Website: goldbondbuilding.com

EMERGENCY TELEPHONE NUMBER

Director Quality Services - National Gypsum Services Company

(704) 551-5820 - 24 Hour Emergency Response

National Gypsum Company is the exclusive service provider for products manufactured by Gold Bond Building Products, LLC.

SECTION 2: HAZARDS IDENTIFICATION

UNITED STATES (US)

According to OSHA 29CFR 1910.1200 (HCS)

GHS CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

PICTOGRAM

None

SIGNAL WORD

None

H/1Fr168t)-12ARen-6Aen-(N)-P2u



CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

panels too high when storing to minimize the risk of falling.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Exposure Limits

COMPONENT	OSHA PEL mg/m³	ACGIH TLV mg/m³			
Calcium Sulfate Dihydrate	15 ^(T) 5 ^(R)	10 ^(T)			
Crystalline Silica ¹	[(10) / (%SiO2+2)] ^(R) : [(30) / (%SiO2+2)] ^(T)	0.025 ^(R)			
Vermiculite	15 ^(T) 5 ^(R)	10 ^(T)			
Fiberglass, synthetic, vitreous, continuous	15 ^(T) 5 ^(R)	1 f/cc ^(R)			
T - Total Dust R - Respirable Dust 1 - Present as an impurity in raw materials.					

EXPOSURE CONTROLS/APPROPRIATE ENGINEERING CONTROLS

Work/Hygiene Practices: Utilize methods to minimize dust production. Utilize wet methods, when appropriate, to reduce generation of dust.

PERSONAL PROTECTIVE EQUIPMENT/RESPIRATORY PROTECTION

A NIOSH approved particulate respirator is recommended in poorly ventilated areas or if the PEL/TLV is exceeded. OSHA's 29 CFR 1910.134 (Respiratory Protection Standard) must be followed whenever work conditions require respirator use.

EYE PROTECTION

Safety glasses or goggles.

SKIN

Gloves, protective clothing and/or barrier creams may be utilized if conditions warrant.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

- a. Appearance: PURPLE coated gypsum board with white/gray core
- b. Odor: None
- c. Odor threshold: Not available
- **d. pH:** ~7
- e. Melting point/freezing point: Not Available
- f. Initial boiling point and boiling range: Not Available
- g. Flash point: Not available

SECTION 12: ECOLOGICAL INFORMATION

- a. Ecotoxicity (aquatic and terrestrial, where available): This product does not present an ecological hazard to the environment.
- b. Persistence and degradability: Unknown
- c. Bioaccumulative potential: Gypsum is a naurally occurring mineral. Biodegradation and/or bioaccumulation potential is not applicable.
- d. Mobility in soil: Unknown
- e. Other adverse effects (such as hazardous to the ozone layer): None known

SECTION 13: DISPOSAL CONSIDERATIONS

This material is not considered a hazardous waste. Dispose of according to Local, State, Federal, and Provincial Environmental Regulations.

SECTION 14: TRANSPORT INFORMATION

This product is not a DOT hazardous material. Shipping Name: Same as product name ICAO/IATA/IMO: Not applicable

SECTION 15: REGULATORY INFORMATION

All ingredients are included on the TSCA inventory.

FEDERAL REGULATIONS

SARA Title III: Not listed under Sections 302, 304, and 313

CERCLA: Not listed **RCRA**: Not listed

OSHA: Dust and potential respirable crystalline silica generated during product use may be hazardous.

State Regulations: California Prop 65: Respirable crystalline silica is known to the state of California to cause cancer. Industrial hygiene monitoring

during recommended use of this product failed to identify any respirable crystalline silica.

Canada WHMIS: All components of this product are included in the Canadian Domestic Substances List (DSL).

SECTION 16: OTHER INFORMATION

SDS PREPARED BY:

Gold Bond Building Products, LLC 2001 Rexford Road Charlotte, NC 28211