

## DATA SHEET

# EcoFill® Wx Blowing Insulation



### DESCRIPTION

EcoFill Wx blowing insulation is an unbonded, fiberglass blowing insulation with a high degree of recycled content, designed for

### APPLICATION

- Open blows in attics
- Dense-pack sidewalls using the drill-and fill-technique

### SPECIFICATION COMPLIANCE

- ASTM C764; Type I
- HH-I-1030B; Class B Certified
- 

### INDOOR AIR QUALITY

- UL Environment
  - GREENGUARD Certified
  - GREENGUARD Gold Certified
  - Validated to be Formaldehyde-Free
- EUCEB Certified

### FIBERGLASS AND MOLD

mold can grow on almost any material when it becomes wet

CONTRACTOR: \_\_\_\_\_  
JOB: \_\_\_\_\_  
DATE: \_\_\_\_\_

### DOING MORE FOR THE WORLD WE LIVE IN.

All of our products are made from sustainable resources, such as recycled glass and sand. And we're proud to be putting glass bottles back to work rather than into landfills. Our products are made with a minimum of 50% recycled glass—totaling an average of 26 million bottles each month.



TECHNICAL DATA		
Property (Unit)	Test	Performance
Corrosion	ASTM C764	Pass
Critical Radiant Flux	ASTM E970	
Combustibility	ASTM E136	Non-combustible
Water Vapor Sorption (by weight)	ASTM C1104	5% maximum
Mold Growth	ASTM C1338	Pass
Surface Burning Characteristics		

[Blue Header Row]					
[Light Blue Cell]	[Light Blue Cell]	[Light Blue Cell]	[Light Blue Cell]	[Light Blue Cell]	[Light Blue Cell]
[Light Blue Cell]	[Light Blue Cell]	[Light Blue Cell]	[Light Blue Cell]	[Light Blue Cell]	[Light Blue Cell]

[Large Empty Cell]	[Large Empty Cell]	[Large Empty Cell]	[Large Empty Cell]	[Large Empty Cell]	[Large Empty Cell]
--------------------	--------------------	--------------------	--------------------	--------------------	--------------------

[Small Empty Cell]
[Small Empty Cell]
[Small Empty Cell]

CERTIFICATIONS

---



---